

## AM2573M 1.3M IR IP Cam (PoE)



### Key Features

1. H.264, and MJPEG encoder
2. 1280x1024 / 1280\*720 resolution, max 30fps
3. IR LED and ICR for day and night surveillance
4. Built in Power over Ethernet
5. Support various protocols: RTSP, UPnP, 3GPP, HTTPS, Samba
6. Event trigger action: Send to NAS, send to FTP, send to Email, notify to HTTP/TCP servers
7. Free bundle 64ch. SecuGuard software

Camera module	
Module Name	AM2573M-A5F2LAO
Effective Pixels	1280 x 1024 pixels
Lens	4.3mm
Lighting LEDs type	IR LED
ICR	Yes
Video	
Video Encoder	H.264 and Motion JPEG simultaneously
Video Mode	1.3M Mode (4:3) and 720p Mode (16:9)
Video Profile	8 profiles simultaneously
Frame Rate	Up to 30fps (NTSC) / 25fps (PAL)
Image Setting	AE, AWB 3D Noise reduction Exposure Value, Color Level, Brightness, Sharpness, Contrast Mirror/Flip Privacy Masks Text, time and date overlay
Streaming	Simultaneously multi-profile streaming Streaming over UDP, TCP, HTTP, or HTTPS M-JPEG streaming over HTTP (server push) Supports 3GPP mobile surveillance (MPEG4) Controllable frame rate and bandwidth Constant and variable bit rate (MPEG4 / H.264)

<b>ROI</b>	2 windows, free scale region of interest
<b>Network</b>	
<b>Ethernet</b>	10/100M auto negotiation
<b>Supported Protocols</b>	IPv6, IPv4, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP
<b>DDNS</b>	DIPS™
<b>NAT Transversal</b>	UPnP NAT transversal
<b>Security</b>	Password protection, IP address filtering, HTTPS encrypted data transmission, user access log
<b>Users</b>	20 simultaneous unicast users
<b>System Integration</b>	
<b>SDK</b>	Open API for software integration <b>ONVIF</b>
<b>Alarm Triggers</b>	Intelligent video motion detection
<b>Motion Detection</b>	Video motion detection up to 10 windows
<b>Alarm Events</b>	<ul style="list-style-type: none"> <li>● File upload via FTP or email</li> <li>● File upload via Samba to NAS</li> <li>● Notification via email, HTTP, and TCP</li> </ul>
<b>Video Buffer</b>	Pre- and post- alarm buffering
<b>General</b>	
<b>Power Supply</b>	Built in Power over Ethernet
<b>Connectors</b>	RJ-45 10BaseT/100BaseTX (Built in Power over Ethernet)
<b>Indication LED</b>	Green and orange LEDs
<b>Operating Temperature</b>	0°C ~ 40°C
<b>Operating Humidity</b>	20% ~ 80% (non-condensing)
<b>Viewing System</b>	
<b>OS</b>	Windows® XP, Vista, Win7, Win8
<b>Browser</b>	IE 6.0 or latter / Firefox / Safari / Chrome
<b>Cell Phone</b>	With 3GPP player, iPhone™, Android™
<b>Video Player</b>	VLC, Quick Time, Real Player, Core Player, iPhone™ & Android™ App
<b>Software</b>	
<b>Search &amp; Installation</b>	IPWizard II
<b>Bundled NVR Program</b>	SecuGuard 6.x: * 64ch. multi-channel supports Tri-decoder <input type="checkbox"/> * 16ch. video playback (synchronization) <input type="checkbox"/> * Smart & re-sizeable digital zoom.

	<ul style="list-style-type: none"><li>* Snapshot and edit</li><li><input type="checkbox"/> * Motion, DI, Scheduler recording</li><li><input type="checkbox"/> * Fast rewind and forward (MPEG4, H.264, MJPEG rewind)</li><li><input type="checkbox"/> * 32x24 motion detection grids</li><li><input type="checkbox"/> * Smart search (by time, by motion )</li><li><input type="checkbox"/> * E-MAP</li><li>* Event schedule setting</li><li>* Remote service</li><li>* Camera tampering</li></ul>
--	--

※ The product design and dimensions may change without previous notice for improvement of performance.