

## PFN-AH2706D H.264 2Mega IR IP Dome



Member of ONVIF

### Key Features

1. 2Mega or 720p resolution, real-time from Sony Exmor™ CMOS image sensor
2. Gigabit (1000Base-T) Ethernet
3. H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
4. H.264 high profile, main profile and baseline
5. Multi-language OSD text
6. Comprehensive I/O ports: MIC in, audio out, video out, DI, DO, RS485, RJ45, mSD
7. Built in ICR for day & night surveillance without color shift
8. Built in Power over Ethernet
9. Event trigger action: Send to NAS, send to FTP, send to Email, voice alert, go preset and tour, notify to HTTP/TCP servers, Send to mSD
10. Free bundle 64ch. SecuGuard software

Camera	
Model No	AH2706D-A2V2AAO
Image Device	Sony Exmor™ image sensor
Effective Pixels	1920x1080 pixels
Lens	3.3-12mm vari-focal lens
IRIS	DC IRIS
IR LED	15M IR distance
ICR	Mechanical
IP Module	
Video	
Video Encoder	H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
Video Profile	12-profile simultaneously @ 2M mode (4:3) 12-profile simultaneously @ 720p mode (16:9) H.264 high profile, main profile and baseline
Profile Setting	Every video profile has Independent CBR/ VBR/ EVBR/ GOP/ Frame rate setting
Frame Rate	Up to 30fps in all resolutions

<b>Region of Interest</b>	Max. 3 ROI @ 2M pixels mode. Editable range Max. 3 ROI @ 720p mode. Editable range
<b>Iris Exposure Control</b>	Auto mode / Outdoor mode / Manual mode Manual mode : 1/2~1/47,000 seconds
<b>Image Setting</b>	AE, AWB <b>3D Noise reduction</b> <b>Digital WDR</b> Color, brightness, sharpness, contrast, Hue Mirror/Flip Privacy Masks Text, time and date overlay Overlay image on video
<b>Streaming</b>	Simultaneously multi-profile streaming Streaming over UDP, TCP, HTTP, or HTTPS M-JPEG streaming over HTTP (server push) Controllable frame rate and bandwidth Constant and variable bit rate (MPEG4 / H.264) Region of Interest (ROI) Aera of Interest (AOI)
<b>Audio</b>	
<b>Audio Encoder</b>	RTSP: G.711 64kbps, G.726 32kbps, AAC (option, by request)
<b>Audio Streaming</b>	One-way or two-way
<b>Microphone</b>	External microphone in
<b>Audio Output</b>	Adjustable audio gain
<b>Network</b>	
<b>Supported Protocols</b>	IPv4, <b>IPv6</b> , TCP, UDP, HTTP, <b>HTTPS</b> , SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, Samba, ICMP, <b>SNMP</b>
<b>Security</b>	Password protection, IP address filtering, HTTPS encrypted data transmission, user access log
<b>Users</b>	20 simultaneous unicast users
<b>Ethernet</b>	10/100/1000M auto negotiation
<b>System Integration</b>	
<b>Application Programming Interface</b>	ONVIF Open API for software integration SDK
<b>Event Detection</b>	<a href="#">Intelligent motion detection</a> <a href="#">digital input</a>

	<a href="#">audio detection</a> <a href="#">Camera tampering</a>
<b>Motion Detection</b>	10-zone video motion detection with included or excluded options
<b>Audio Detection</b>	Audio level 0- 100 .
<b>Event Trigger</b>	<ul style="list-style-type: none"> <li>● File upload via FTP or email</li> <li>● File upload via Samba to NAS</li> <li>● Notification via email, HTTP, and TCP</li> <li>● External output activation</li> <li>● Audio alerting output</li> <li>● mSD card local storage</li> </ul>
<b>Video Buffer</b>	Pre- and post- alarm buffering
<b>General</b>	
<b>RAM</b>	256MB
<b>ROM</b>	16MB
<b>Power Supply</b>	12V DC external power adapter
<b>PoE</b>	IEEE 802.3af Class 3
<b>Connectors</b>	RJ-45 10Base-T/100Base-TX/1000Base-T 12VDC power jack 1 alarm input and 1 output RS485 Audio out External MIC input Video out Factory default reset mSD card
<b>Mounting</b>	Side-out (via cable) and ceiling-out (via connector board)
<b>Indication LED</b>	Green and orange LEDs
<b>Construction</b>	Indoor use
<b>Operating Temperature</b>	<b>-10°C to 40°C</b>
<b>Operating Humidity</b>	20% ~ 80% (non-condensing)
<b>Viewing System</b>	
<b>OS</b>	Windows® XP, Vista, 7, 8
<b>Browser</b>	IE 6.0 or later, Firefox 2.0 or later, Safari , Google Chrome
<b>Video Player</b>	VLC, Quick Time, Real Player, Core Player
<b>Software</b>	
<b>Search &amp; Installation</b>	IP Wizard II

Easy DDNS	DIPS™
<b>Bundled NVR Program</b>	64ch. SecuGuard™ <input type="checkbox"/> * 64ch. multi-channel supports Tri-decoder <input type="checkbox"/> * 16ch. video playback (simultaneously) <input type="checkbox"/> * Smart & scrollable digital zoom. Snapshot and edit <input type="checkbox"/> * Motion, DI, Scheduler recording <input type="checkbox"/> * Fast rewind and forward (MPEG4, H.264, MJPEG rewind) <input type="checkbox"/> * 32x24 motion detection grids <input type="checkbox"/> * Smart search (by time, by motion ) <input type="checkbox"/> * E-MAP * Event schedule setting * Remote service * Camera tampering
<b>Bundle Mobile Phone APPS</b>	SecuAngel (Android) and iVanguard (iOS)

※ The product design and dimensions may change without previous notice for improvement of performance.