info@pfngroup.com

TEL: 021_ 88972211

FAX: 021_88985950

PFN-AM2570D H.264 2 Mega Bullet IR IP Camera





Key Features

- H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
- 2. 1080p resolution, real-time (Full HD)
- Comprehensive I/O ports: MIC in, audio out, video out, DI, DO, RS485, RJ45
- Built in IR LED and ICR for day & night surveillance without color shift, controlled by photo sensor
- 5. Built in Power over Ethernet
- 6. IP66 weather proof construction
- Support various protocols: RTSP, UPnP, 3GPP, HTTPS, Samba
- Event trigger action: Send to NAS, Send to FTP, send to Email, Voice alert, Notify to HTTP/TCP servers
- 9. Free bundle 64ch. SecuGuard software

Camera	
Image Device	2 Mega-pixel image sensor
Effective Pixels	1920x1080 pixels (sensor)
Lens	f:4.2mm
IP Module	
Video	
Video Encoder	H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
Video Profile	20 profiles simultaneously @ 2 MEGA Mode
	15 profiles simultaneously @ 720p Mode
Profile Setting	Every video profile has Independent CBR/ VBR/ EVBR/ ECBR/
	GOP/ Frame rate setting
Frame Rate	Up to 30fps for all resolutions (2M Real-time)
Region of Interest	Max. 2 ROI @ 2M pixels mode. Editable range
	Max. 3 ROI @ 720p mode. Editable range
Iris Exposure Control	Auto Iris / Auto Exposure / Hold Exposure / Manual Exposure /
	Outdoor (Manual mode : 1/2~1/32,000 seconds)
Image Setting	AE, AWB

	3D Noise reduction
	Digital WDR
	Exposure Value, Color, Hue, Brightness, Contrast, Sharpness
	Mirror/Flip
	Privacy Masks
	Text, time and date overlay
Streaming	Simultaneously multi-profile streaming
	Streaming over UDP, TCP, HTTP, or HTTPS
	M-JPEG streaming over HTTP (server push)
	Supports 3GPP mobile surveillance (MPEG4)
	Controllable frame rate and bandwidth
	Constant and variable bit rate (MPEG4 / H.264)
	Region of Interest (ROI)
Audio	
Audio Encoder	RTSP: G.711 64kbps, G.726 32kbps
Audio Streaming	One-way or two-way
Microphone	External microphone
Audio Output	Adjustable audio gain
Network	
Supported Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS,
	DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP,
	IGMP, PPPoE, 3GPP, Samba, ICMP
Socurity	Password protection, IP address filtering, HTTPS encrypted data
Security	transmission, User access log
Users	20 simultaneous unicast users
Ethernet	10/100M auto negotiation
System Integration	
Ammliantina	ONVIF
Application	Open API for software integration
Programming Interface	SDK
Event Detection	
	Intelligent motion detection
M .: B:	Intelligent motion detection Audio detection
Maria Danis	
Motion Detection	Audio detection
Motion Detection Audio Detection	Audio detection 10-zone video motion detection with included or excluded
	Audio detection 10-zone video motion detection with included or excluded options

	Notification via email, HTTP, and TCP
	External output activation
	Audio alerting output
Video Buffer	Pre- and post- alarm buffering
General	
RAM	256MB
ROM	16MB
Power Supply	12V DC external power adapter
PoE	IEEE 802.3af Class 3
	RJ-45 10BaseT/100BaseTX
	12VDC power jack
	1 alarm input and 1 output
Connectors	RS485
Connectors	Audio out
	Built in MIC & External MIC input
	Composite Video out
	Factory default reset
Indication LED	Green and orange LEDs
Operating Temperature	-10°C to 40°C
Operating Humidity	20% ~ 80% (non-condensing)
Viewing System	
os	Windows® XP, Vista, 7, 8
Browser	IE 6.0 or later, Firefox 2.0 or later, Safari , Google Chrome
Cell Phone	With 3GPP player
Video Player	VLC, Quick Time, Real Player, Core Player
Software	
Search & Installation	IP Wizard II
Easy DDNS	DIPS™
Bundled NVR Program	64ch. SecuGuard™ □
	* 64ch. multi-channel supports Tri-decoder
	□* 16ch. video playback (simultaneously)
	□* Smart & scrollable digital zoom. Snapshot and edit
	□* Motion, DI, Scheduler recording
	□* Fast rewind and forward (MPEG4, H.264, MJPEG rewind)
	□* 32x24 motion detection grids
	□* Smart search (by time, by motion)
	□*E-MAP

	* Event schedule setting * Remote service * Camera tampering
Bundle Mobile Phone APPS	SecuAngel (Android) and iVanguard (iOS)

 $[\]divideontimes$ The product design and dimensions may change without previous notice for improvement of performance.