info@pfngroup.com

TEL: 021\_ 88972211

FAX: 021\_88985950

## PFN-AH2030T H.264 3Mega Vandal IR IP Dome





## **Key Features**

- 3Mega or 1080p resolution, real-time from Sony Exmor™ CMOS image sensor
- 2. Gigabit (1000Base-T) Ethernet
- H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
- 4. H.264 high profile, main profile and baseline
- 5. Multi-language OSD text
- Comprehensive I/O ports: MIC in, audio out, video out, DI, DO, RS485, RJ45, uSD
- Built in ICR for day & night surveillance without color shift
- 8. Built in Power over Ethernet
- Event trigger action: Send to NAS, send to FTP, send to Email, voice alert, go preset and tour, notify to HTTP/TCP servers
- 10. Free bundle 64ch. SecuGuard software

Camera	
Model No	AH2030T-A6V1AAO
Image Device	Sony Exmor™ 3.4 Mega-pixel image sensor
Effective Pixels	2048x1536 pixels
Lens	3∼9 mm vari-focal lens
Low Lux	0.5 lux @ F1.4
IRIS	DC IRIS
IR LED	15M IR distance
ICR	Mechanical
IP Module	
Video	
Video Encoder	H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
Video Profile	8-profile simultaneously @ 3M mode (4:3)
	12-profile simultaneously @ 1080 mode (16:9)
	H.264 high profile, main profile and baseline
Profile Setting	Every video profile has Independent CBR/ VBR/ EVBR/ GOP/
	Frame rate setting

Erama Data	Up to 30fps in all resolutions
Frame Rate	Up to 30fps in all resolutions
Region of Interest	Max. 2 ROI @ 3M pixels mode. Editable range
	Max. 3 ROI @ 1080p mode. Editable range
Iris Exposure Control	Auto mode / Outdoor mode / Manual mode
	Manual mode : 1/2~1/47,000 seconds
	AE, AWB
Image Setting	3D Noise reduction
	Digital WDR
	Color, brightness, sharpness, contrast, Hue
	Mirror/Flip
	Privacy Masks
	Text, time and date overlay
	Overlay image on video
Streaming	Simultaneously multi-profile streaming
	Streaming over UDP, TCP, HTTP, or HTTPS
	M-JPEG streaming over HTTP (server push)
	Controllable frame rate and bandwidth
	Constant and variable bit rate (MPEG4 / H.264)
	Region of Interest (ROI)
	Aera of Interest (AOI)
Audio	
Audio Encoder	RTSP: G.711 64kbps, G.726 32kbps, AAC (option, by request)
Audio Streaming	One-way or two-way
Microphone	External microphone in
Audio Output	Adjustable audio gain
Network	
	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS,
Supported Protocols	DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP,
	IGMP, PPPoE, Samba, ICMP, <b>SNMP</b>
Security	Password protection, IP address filtering, HTTPS encrypted data
Security	transmission, user access log
Users	20 simultaneous unicast users
Ethernet	10/100/1000M auto negotiation
System Integration	
Annliaction	ONVIF
Application	Open API for software integration
Programming Interface	SDK
L	L

	T
Event Detection	Intelligent motion detection
	digital input
	audio detection
	Camera tampering
Motion Detection	10-zone video motion detection with included or excluded
	options
Audio Detection	Audio level 0- 100 .
	File upload via FTP or email
	File upload via Samba to NAS
Event Trigger	Notification via email, HTTP, and TCP
	External output activation
	Audio alerting output
	mSD card local storage
Video Buffer	Pre- and post- alarm buffering
General	
RAM	256MB
ROM	16MB
Power Supply	12V DC external power adapter
PoE	IEEE 802.3af Class 3
	RJ-45 10Base-T/100Base-TX/1000Base-T
	12VDC power jack
	1 alarm input and 1 output
	RS485
Connectors	Audio out
	External MIC input
	Video out
	Factory default reset
	mSD card
Mounting	Side-out (via cable) and ceiling-out (via connector board)
Indication LED	Green and orange LEDs
Construction	Outdoor use
Operating Temperature	-10°C to 40°C
Operating Humidity	20% ~ 80% (non-condensing)
Viewing System	
os	Windows® XP, Vista, 7, 8
Browser	IE 6.0 or later, Firefox 2.0 or later, Safari , Google Chrome
Video Player	VLC, Quick Time, Real Player, Core Player

Software	
Search & Installation	IP Wizard II
Easy DDNS	DIPS™
Bundled NVR Program	64ch. SecuGuard™ □
	* 64ch. multi-channel supports Tri-decoder
	□* 16ch. video playback (simultaneously)
	□ * Smart & scrollable digital zoom. Snapshot and edit
	□* Motion, DI, Scheduler recording
	□* Fast rewind and forward (MPEG4, H.264, MJPEG rewind)
	□* 32x24 motion detection grids
	□* Smart search (by time, by motion)
	□* E-MAP
	* Event schedule setting
	* Remote service
	* Camera tampering
Bundle Mobile Phone	SecuAngel (Android) and iVanguard (iOS)
APPS	

**X** The product design and dimensions may change without previous notice for improvement of performance.