



TEL: 021\_ 88972211

FAX: 021\_88985950

## PFN-AH2630T H.264 3Mega BOX IP Camera





## **Key Features**

- 3Mega or 1080p resolution, real-time from Sony Exmor™ CMOS image sensor
- 2. Gigabit (1000Base-T) Ethernet
- 3. H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
- 4. H.264 high profile, main profile and baseline
- 5. Multi-language OSD text
- Comprehensive I/O ports: MIC in, audio out, video out, DI, DO, RS485, RJ45, uSD
- Built in ICR for day & night surveillance without color shift
- 8. Built in Power over Ethernet
- Event trigger action: Send to NAS, send to FTP, send to Email, voice alert, go preset and tour, notify to HTTP/TCP servers
- 10. Free bundle 64ch. SecuGuard software

Camera	
Image Device	Sony Exmor™ 3.4 Mega-pixel image sensor
Effective Pixels	2048x1536 pixels
Lens	CS mount
Low Lux	0.5lux@F1.4
IRIS	Support DC & Auto IRIS Lens
IP Module	
Video	
Video Encoder	H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
Video Profile	8 profiles simultaneously @ 3 MEGA Mode
	12 profiles simultaneously @ 2 MEGA mode(1080p Mode)
Profile Setting	Every video profile has Independent CBR/ VBR/ EVBR/ GOP/
	Frame rate setting
Frame Rate	Up to 30fps @ 3M pixels mode (4:3)
	Up to 30fps @ 1080p mode (16:9)
Region of Interest	Max. 2 ROI @ 3M pixels mode. Editable range
	Max. 3 ROI @ 1080p mode. Editable range

	1
Iris Exposure Control	Auto Iris / Auto Exposure / Hold Exposure / Manual Exposure /
	Outdoor (Manual mode : 1/2~1/47,000 seconds)
Image Setting	AE, AWB
	3D Noise reduction
	Digital WDR
	Exposure Value, Color, brightness, sharpness, contrast, Hue
	Mirror/Flip
	Privacy Masks
	Text, time and date overlay
	Overlay image on video
Streaming	Simultaneously multi-profile streaming
	Streaming over UDP, TCP, HTTP, or HTTPS
	M-JPEG streaming over HTTP (server push)
	Controllable frame rate and bandwidth
	Constant and variable bit rate (MPEG4 / H.264)
	Region of Interest (ROI)
	Aera of Interest (AOI)
Audio	
Audio Encoder	RTSP: G.711 64kbps, G.726 32kbps, AAC (option, by request)
Audio Streaming	One-way or two-way
Microphone	Built-in and external microphone
Audio Output	Adjustable audio gain
Network	
	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS,
Supported Protocols	DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP,
	IGMP, PPPoE, Samba, ICMP, <b>SNMP</b>
Casumitur	Password protection, IP address filtering, HTTPS encrypted data
Security	transmission, user access log
Users	20 simultaneous unicast users
Ethernet	10/100/1000M auto negotiation
System Integration	
Application	ONVIF
	Open API for software integration
Drogramming Interface	-   -   -   -   -   -   -   -   -   -
Programming Interface	SDK
Programming Interface	
Programming Interface  Event Detection	SDK

	<del> </del>
Motion Detection	10-zone video motion detection with included or excluded options
Audio Detection	Audio level 0- 100 .
Event Trigger	<ul> <li>File upload via FTP or email</li> <li>File upload via Samba to NAS</li> <li>Notification via email, HTTP, and TCP</li> <li>External output activation</li> <li>Audio alerting output</li> <li>mSD card local storage</li> </ul>
Video Buffer	Pre- and post- alarm buffering
General	
RAM	256MB
ROM	16MB
Power Supply	12V DC external power adapter
PoE	IEEE 802.3af Class 3
Connectors	RJ-45 10Base-T/100Base-TX/1000Base-T 12VDC power jack AC24V Terminal (option) 1 alarm input and 1 output RS485 Audio out External MIC input Composited video out Factory default reset mSD card
Indication LED	Green and orange LEDs
Operating Temperature	-10°C to 40°C
Operating Humidity	20% ~ 80% (non-condensing)
Viewing System	
os	Windows® XP, Vista, 7, 8
Browser	IE 6.0 or later, Firefox 2.0 or later, Safari , Google Chrome
Video Player	VLC, Quick Time, Real Player, Core Player
Software	
Search & Installation	IP Wizard II
Easy DDNS	DIPS™
Bundled NVR Program	64ch. SecuGuard™ □  * 64ch. multi-channel supports Tri-decoder

	□* 16ch. video playback (simultaneously)
	□* Smart & scrollable digital zoom. Snapshot and edit
	□* Motion, DI, Scheduler recording
	□ * Fast rewind and forward (MPEG4, H.264, MJPEG rewind)
	□* 32x24 motion detection grids
	□* Smart search (by time, by motion)
	□* E-MAP
	* Event schedule setting
	* Remote service
	* Camera tampering
Bundle Mobile Phone	Secure and (Android) and illanguard (iOS)
APPS	SecuAngel (Android) and iVanguard (iOS)

**X** The product design and dimensions may change without previous notice for improvement of performance.